

### 1. Identification

**Product identifier :** SolvECO Surface remover  
**Code :**  
**Supplier :** SuperDécapant Inc.  
**Address:** 619 Rue du Luxembourg  
 Granby, Québec  
 Canada, J2J 2V2

**Contact :** 514 498-3620 Monday to Friday 8h30 to 16h30  
**Recommended use :** Powerful paint stripper with methylene chloride  
**Restrictions on use :** For professional use only.

### 2. Hazard identification

**Warning statement :** DANGER

**Classification**



Carcinogenicity	Category 1B
Reproductive toxicity	Category 1B
Skin irritant	Category 2
Eye irritant	Category 2A
Skin sensitizer	Category 1 B

**Hazard Statement**

H350	May cause cancer
H315+ 320	Causes serious eye and skin irritation
H360	May damage fertility or the unborn child
H317	May cause an allergic skin reaction

**Precautionary statement(s)**

**Prevention:** Avoid breathing vapours and spray. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye and face protection. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product.

**Response:** In case of fire: Use an appropriate extinguisher. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice. IF exposed or concerned: Get medical advice/attention.

**Storage:** Store locked-up in a well-ventilated place. Keep cool.

**Disposal:** Dispose of contents/container in accordance with local, regional, national and/or international regulations in force.

See toxicological information, section 11

### 3. Composition

CAS :	Component	Concentration % (w/w)
75-09-2	Methylene chloride, dichloromethane	80 - 100
64-17-5	Ethanol, Ethyl alcohol	7 - 13
100-51-6	Benzyl alcohol	1 - 5
68956-56-9	Terpene hydrocarbons	1 - 5

Note. Exact percentages are withheld as trade secret

### 4. First aid

If swallowed, irritation, any type of overexposure or symptoms of overexposure occur during use of the product or persists after use, immediately contact a POISON CENTER, an EMERGENCY ROOM or a PHYSICIAN; ensure that the product safety data sheet is available.

**Eye contact:** Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

**Skin contact:** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

**Inhalation:** Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

**Ingestion:** Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

**Symptoms:** Cough, breathing pain, eye redness and skin edema. Headaches, nausea, vomiting and dizziness can also be observed.

**Effects (acute or delayed):** May cause irritation of eyes, skin and respiratory tract

**Immediate medical attention and special treatment: IF MISUSED THIS PRODUCT CAN BE A ASPHYXIATING AGENT.** This product can act as a carrier for skin absorptions of toxins. Some toxins that are not known to be absorbed through skin can readily be absorbed by the use of this carrier. Treat symptomatically with a special care for skin permeation of other unsuspected substances.

### 5. Fire fighting measures

**Suitable extinguishing media:** Use dry chemical, CO2, water spray (fog) or foam.

**Unsuitable extinguishing media:** DO NOT use direct water jets to extinguish this fire

**Specific hazards arising from the hazardous product:** This product is non-flammable in normal condition, however, in case of a fire, it will releases acidic fumes

**Hazardous combustion products:** Hydrogen chloride, phosgene, Carbon monoxide and dioxide.

**Special protective equipment and precautions for fire-fighters:** Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Care must be taken to protect against **acidic fumes**.

### 6. Accidental release measures.

**Personal precautions.** Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate, closely monitor O2 levels as this product could become asphyxiant. Put on appropriate personal protective equipment

**Protective equipment and emergency procedures:** Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

**Methods and materials for containment and cleaning up:** Stop leak if without risk. Move any sensitive equipment from spill area. Dilute with water and mop up as the mixture is water soluble. Alternatively, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion proof equipment. Dispose of via a licensed waste disposal contractor.

### 7. Handling and storage

**Safe handling precautions:** Put on appropriate personal protective equipment, such as thick nitrile gloves (not disposable examination gloves) (see Section 8 for details). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid contact with eyes, skin and clothing. Do not ingest. Avoid breathing vapors. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate, such as a PPRE equipped with organic vapor cartridges. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical equipment in the surrounding environment. Do not reuse container.

**Conditions for safe storage:**

Store in accordance with local regulations as flammable material. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

**Incompatibilities:** Strong reducers, metal powders, Oxidizers. Strong bases and strong acids.

### 8. Exposure control

**RSST Schedule 1:**

CAS :	Hazardous component	%	IDHL (C)		TWA		STEL	
			ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
75-09-2	Methylene chloride, dichloromethane	80 - 100	--	--	50 **	174**	--	--
100-51-6	Benzyl alcohol	7 - 13	--	--	--	--	--	--
68956-56-9	Terpene hydrocarbons	1 - 5	--	--	--	--	--	--
64-17-5	Ethanol, Ethyl alcohol	1 - 5	3300	6217	--	--	1000	1884

\*\*C2 and EM marks for this product, (probable carcinogen, and minimal exposure mandatory)

IDHL: Immediately Dangerous to Life or Health Concentrations

TWA : Time Weighted Average

STEL: Short -Term Exposure Limit

C: Ceiling Limit

**Appropriate engineering controls:** Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Individual protection measures:** Wash hands, forearms and face thoroughly after handling chemical products. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Always have an eyewash station or apparatus nearby.

**Eyes:** DO NOT WEAR CONTACT LENSES Wear anti-splash safety goggles.

**Hands:** Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products disposable examination gloves are typically not suitable for this product, thicker gloves must be considered.

**Respiratory:** If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators equipped with organic vapor cartridges.. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

**Others:** Wear protective clothing with long sleeves and appropriate safety shoes at all times.

## 9. Physical and chemical properties

**Physical state:** Viscous liquid

**Odour:** Ethereal

**Odour threshold:** 214 ppm

**pH:** Neutral when mixed with water

**Melting/Freezing point:** <-97. °C

**Initial boiling point/boiling range:** 40 °C

**Flash point:** Non Flammable in ambient conditions

**Lower flammable/explosive limit:** --

**Upper flammable/explosive limit:** --

**Auto-ignition temperature:** > 400 °C

**Evaporation rate:**< 2.2 (butyl acetate =1)

**Vapour pressure:** < 173 mm Hg at 20 °C

**Vapour density:** > 1 (air=1)

**Relative density:** 1.2 kg/L at 20 °C (water = 1)

**Solubility in water:** Partial

**Partition coefficient - n-octanol/water:** mixture, not applicable

**Decomposition temperature:** Ignites

**Kinematic viscosity:** > 20 mPa s at 25 °C

## 10. Reactivity and Stability

**Reactivity:** Stable under recommended conditions of storage and handling. However, constant sun exposure can lead to carbon monoxide, hydrogen chloride and phosgene formation and exposure to strong acids will generate formaldehyde. Exposure to strong bases may lead to explosive polymerisation.

**Chemical stability:** The product is chemically stable under normal conditions.

**Possible hazardous reactions:** Danger of explosion when heated or if mixed with incompatible substances (acid, bases and oxidizers).

**Conditions to avoid:** Keep away from ignition sources and from incompatible products such as acids, bases and oxidizers.

**Incompatible materials:** This product readily dissolves certain plastics (ABS, PVC, PC) and will also attack certain coatings. It does not attack any metals.

**Hazardous decomposition products:** Carbon monoxide and dioxide, formaldehyde, phosgene, hydrogen chloride

## 11. Toxicological information

	LD <sub>50</sub> oral mg/kg	LD <sub>50</sub> Dermal mg/kg	LC <sub>50</sub> 4h gas ppmV	LC <sub>50</sub> 4h vapours mg/l	LC <sub>50</sub> 4h Dusts mists mg/l
ETA <sub>product</sub>	> 2100 mg/kg	> 2000 mg/kg	N/A	> 20 mg/l	> 5 mg/l

CAS :	Hazardous component	LD <sub>50</sub> oral mg/kg	LD <sub>50</sub> Dermal mg/kg	LC <sub>50</sub> ppmV 4h - gas	LC <sub>50</sub> mg/l 4h vapours	LC <sub>50</sub> mg/l 4h - Dusts mists
75-09-2	Methylene chloride	2000	> 2000	--	49.5	> 15.00
100-51-6	Benzyl alcohol	1610	> 2000	--	--	> 4,178
68956-56-9	Terpene hydrocarbons	5300	> 5000	--	> 20	> 15.00
64-17-5	Ethanol, Ethyl alcohol	7100	> 2000	--	> 20	> 15.00

**Probable exposure route :** This product is absorbed through the respiratory tract, skin and gastrointestinal tract.

**Symptoms:** Cough, breathing pain, eye redness and skin edema. Headaches, nausea, vomiting and dizziness can also be observed.

**Delayed and immediate effects:** May cause irritation of eyes, skin and respiratory tract. Can cause cancer.

**Special precaution:** This product can act as a carrier for skin absorptions of toxins. Some toxins that are not known to be absorbed through skin can readily be absorbed by the use of this carrier. Treat symptomatically with a special care for skin permeation of other unsuspected substances.

## 12. Ecological information

### Ecotoxicity

CAS :	Hazardous component	%	Short term aquatic toxicity CL50	long term aquatic toxicity CE50	Terrestrial toxicity
75-09-2	Methylene chloride	80 - 100	27 mg /L	6-13.3 mg/L	Very low
100-51-6	Benzyl alcohol	7 - 13	460 mg /L	51 mg /L	Very low
68956-56-9	Terpene hydrocarbons	1 - 5	2.1 mg / L	Chronic cat 2 extrapolated from acute toxicity results	Low
64-17-5	Ethanol, Ethyl alcohol	1 - 5	13 000 mg /L (S.gairdneri)	Not deemed necessary	Very low

### Other related information

CAS :	Hazardous component	%	Persistence	Biodegradability	Bioaccumulation potential
75-09-2	Methylene chloride	80 - 100	Non persistent	Readily biodegradable	Negligible
100-51-6	Benzyl alcohol	7 - 13	Non persistent	Readily biodegradable	Negligible
68956-56-9	Terpene hydrocarbons	1 - 5	Non persistent	Readily biodegradable	Possible
64-17-5	Ethanol, Ethyl alcohol	1 - 5	Non persistent	Readily biodegradable	Negligible

### 13. Disposal considerations

**Methods of disposal:** The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor as a **toxic waste**. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

### 14. Transport information

	TDG	DOT	IMDG	IATA
UN Number	UN1593	UN1593	UN1593	UN1593
Proper Shipping name	DICHLOROMETHANE	DICHLOROMETHANE	DICHLOROMETHANE	DICHLOROMETHANE
Hazard class	6.1	6.1	6.1	6.1
Packaging group	III	III	III	III

Marine pollutant : No

Limited quantity exemption maximum capacity per container : 5 L

### 15. Regulatory information

Illigible VOC Content : < 30%

Canada

CAS :	Hazardous Component	%	DSL	NDSL	NPRI
75-09-2	Methylene chloride	80 - 100	X		X
100-51-6	Benzyl alcohol	7 - 13	X		X
68956-56-9	Terpene hydrocarbons	1 - 5	X*		X
64-17-5	Ethanol, Ethyl alcohol	1 - 5	X		X

\* All components of CAS 68956-56-9 are within DSL and TSCA

### 16. Other information

Date : 8/7/2024

Version : 1

Notice to the reader: The manufacturer hereby declares he has no control over the that the information disclosed herein have been based information on derived governmental sites. The manufacturer does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. Classifications of hazards and advices given by this document are based on regulatory calculations and professional judgement of governmental data and other sources being considered credible. Even with the best of care, research and expertise it is impossible to guarantee that no other undisclosed hazards exist. By this data sheet, the manufacturer hereby discloses all the potential dangers it has knowledge of and which might be related to the product in order to allow the proper care to be brought and use with regard to the product.

Additional information exceeding regulatory requirements are added to further help proper handling of the product. Failure to follow hereby proper care involving the given information can lead to injury and even death. The manufacturer assumes no responsibility for personal and/or material damage, lost or injury of whichever nature caused or which may occur following the wrongful, inappropriate, negligent or abusive use or handling of the product or from not having read the herein contained information.

Reader must also bear in mind that science is constantly evolving and that new information may emerge after the production of this safety data sheet. It is responsibility of the user to make sure he has updated information in hand by verifying dates and versions of the safety data sheets.