

**WOOD PREP**

WPB-O1 / WPB-4

**BEFORE YOU START: SAFETY AND HANDLING**

- It is a highly flammable product that must be handled with care.
- **NEVER** use it in an enclosed space. **ONLY work** in well-ventilated area, ensuring a continuous supply of fresh air. Do not breathe in the product vapors.
- **DO NOT use** on fiberglass, vinyl, linoleum, rubber, acrylic, and plastics.
- **NOT INTENDED** for use as a glass cleaner, windshield washer fluid, or gas line antifreeze. This product is formulated specifically for wood preparation.

**WASTE MANAGEMENT**

- Product classified as flammable. Do not dispose of the content or container in household garbage. Take them to an ECO CENTER or dispose of them according to current local environmental regulations.
- Once the container is fully empty, you can let it dry completely, then dispose of the empty dry container in the recycling without the cap.

**WOOD PREP can be used for the following:**

- Replaces Methyl Hydrate for cleaning after stripping with any paint stripper
- Clean wood after sanding without opening the grain
- Prepares the wood before staining
- Cleans out Oil paints, Shellac, Teak Oil, Urethanes.
- Can also be used to clean Urethane Foam (Wet or Dry)

**STEP 1 SAFE PREPARATION**

Set up your work area in a perfectly ventilated space.

Put on all your personal protective equipment (gloves, goggles, protective clothing).

**OPENING TIP**

The container may be under internal pressure. Always place a cloth over the safety seal to block any potential splashes, then carefully follow the procedure illustrated on the cap to open it safely.

STEP 2 APPLICATION

- Apply the SolvEco® WOOD PREP directly onto your clean cloth or chosen applicator.

STEP 3 DEEP CLEANING

- Wipe the wood surface firmly after stripping or sanding.
- This action dissolves and lifts residues, grease, contaminants, or traces of old coatings (epoxies, shellacs, teak oils, urethanes, and water-based paints).

STEP 4 DRYING

- Allow the surface to dry completely.
- Thanks to its high-performance, residue-free formula, the product evaporates cleanly. The wood is immediately spotless and ready for its new finish, paint, or coating.

STEP 5 TOOL MAINTENANCE

- Use the pure product to rinse, clean, and effectively remove residue from your brushes and rollers after completing the work.
- It will remove Oil-Based paints, Shellac, Teak Oil and Urethanes.

STEP 6 STORAGE

- Wipe away any excess liquid from around the neck of the container.
- Close the cap tightly and securely after each use.
- Store the container in a cool place.



MADE IN CANADA BY :

SUPER REMOVER / DÉCAPANT INC.

619, rue du Luxembourg, Granby (Québec) J2J 2V2 Canada

Phone.: 1 (450) 770-2948

Toll free (Canada only): 1 (866) 772-2948

info@superdecapant.com

